



HP	A	B	C	D	E	F	G	H
30 (286TSC)	$29 \frac{15}{16}$	$9 \frac{5}{8}$	16	$40 \frac{3}{16}$	$8 \frac{1}{8}$	$19 \frac{7}{8}$	$4 \frac{15}{16}$	$10 \frac{1}{2}$
40 (324TSC)	$30 \frac{15}{16}$	$9 \frac{7}{8}$	16	$40 \frac{3}{16}$	$14 \frac{5}{8}$	$20 \frac{11}{16}$	$1 \frac{11}{16}$	$10 \frac{1}{2}$
50 (326TSC)	$32 \frac{7}{16}$	$9 \frac{7}{8}$	16	$40 \frac{3}{16}$	$14 \frac{5}{8}$	$20 \frac{11}{16}$	$1 \frac{11}{16}$	$10 \frac{1}{2}$
60 (364TSC)	$34 \frac{5}{8}$	$12 \frac{1}{2}$	$11 \frac{1}{4}$	$40 \frac{3}{16}$	14	$25 \frac{5}{16}$	2	$10 \frac{1}{2}$
75 (365TSC)	$34 \frac{5}{8}$	$12 \frac{1}{2}$	$12 \frac{1}{4}$	$40 \frac{3}{16}$	14	$25 \frac{5}{16}$	2	$10 \frac{1}{2}$

HP	Est. WGT. (lbs)
30 (286TSC)	450
40 (324TSC)	517
50 (326TSC)	575
60 (364TSC)	877
75 (365TSC)	934

Retro Kit Est. WGT. (lbs)	280
---------------------------	-----

\*\*Dependent on blower pulley size.  
Maximum dimension shown.  
(Minimum is 1-1/2 in. less)